## STORMWATER POST-CONSTRUCTION TREATMENT DEVICE OPERATIONS & MAINTENANCE

## Fire Station # 27 613 Old Telegraph Rd, Fillmore

Devices On-Site:
Bioretention
Catch Basin Insert









## **Operations & Maintenance Plan**

O & M Person  ### Pre-Wet Se  (before Oc.)	ason	Post-Wet So	eason After Storm	
Bioretention				
Activity	O & M Needed	O & M Completed	Comments / Maintenance Perform	
Remove Trash/Debris/Sediment				
Assess for Poor Vegetative Health (i.e. Weeds, loss of ground cover, grass > 6" tall or mulch outside 2"-4" range)				
Repair Erosion/Scouring				
Repair and Clear Blockages of Inlet/Overflow Pipes				
If Standing Water is present 4 days after rain event, maintenance is needed immediately to restore infiltration. (See Planting/Storage Media details in 2011 Technical Guidance Manual Chapter 6 Page 44)				

<sup>&#</sup>x27;2011 Technical Guidance Manual is available under Publications/Manuals @ http://vcstormwater.org

Catch Basin Insert					
Activity	O & M Needed	O & M Completed	Comments / Maintenance Performed		
Remove Trash/Debris/Sediment					
Inspect for Tears, Holes, Bending, and Missing Hangers					
Replace Filter Medium Pouches Annually					

http://www.kristar.com/ \*(1) Model M-22